


BANANZA®

Direct-Fired Air Handler



B-Series Dimension and Selection Guide

1.800.536.3461
www.bananza.com




Intertek

ANSI Z83.4/CSA 3.7 100% OUTSIDE AIR
(US & CANADA)

Z83.18 - RECIRCULATION (US)

ANSI Z83.25/CSA 3.19 PROCESS HEATER
(US & CANADA)

Upright Model



DIMENSIONS

Model		A	B	C	D	E	F	G	H	J	K	L	M1*	M2*	P	T1	T2	U	V1	V2	W1*	W2*	Y	Z
B-350 1K-2K CFM	(in) (cm)	28.3 (71.8)	81.7 (207.5)	11.8 (29.9)	10.2 (25.9)	9.2 (23.3)	8.3 (21.0)	16.0 (40.6)	6.1 (15.5)	15.1 (38.4)	25.3 (64.2)	4.7 (12.0)	134.8 (342.4)	168.7 (428.5)	32.2 (81.8)	20.8 (52.8)	3.1 (7.9)	18.0 (28.4)	7.3 (18.5)	7.3 (18.5)	33.2 (84.3)	40.7 (103.4)	43.5 (110.5)	28 (71.1)
B-350 3K-5K CFM	(in) (cm)	28.3 (71.8)	81.7 (207.5)	15.6 (39.6)	13.5 (34.2)	9.2 (23.3)	6.1 (15.5)	16.0 (40.6)	6.1 (15.5)	15.1 (38.4)	25.3 (64.2)	4.7 (12.0)	134.8 (342.4)	168.7 (428.5)	32.2 (81.8)	15.7 (39.8)	3.0 (7.6)	18.0 (28.4)	7.3 (18.5)	7.3 (18.5)	33.2 (84.3)	40.7 (103.4)	43.5 (110.5)	28 (71.1)
B-650	(in) (cm)	43.3 (109.9)	106.6 (270.7)	23.1 (58.7)	25.0 (63.5)	11.2 (28.4)	10 (25.4)	32 (81.3)	5.6 (14.2)	15.0 (38.1)	39.0 (99.0)	4.15 (10.5)	159.6 (405.4)	193.6 (491.7)	40.2 (102.1)	11.9 (30.2)	3.4 (8.6)	23.3 (59.2)	8.1 (20.6)	3.4 (8.6)	41.3 (104.9)	65.4 (166.1)	45.8 (116.3)	26.0 (66.0)
B-1000	(in) (cm)	49.1 (124.7)	97.8 (248.4)	27.6 (70.1)	27.8 (70.6)	12.8 (32.5)	10.8 (27.4)	40.5 (102.8)	4.3 (10.9)	15.0 (38.1)	43.1 (109.4)	2.8 (7.1)	150.8 (383.0)	184.8 (469.4)	44.3 (112.5)	13.7 (34.7)	3.2 (8.1)	20.0 (51.0)	8.2 (20.8)	3.4 (8.6)	45.7 (116.1)	65.0 (165.1)	43.25 (109.9)	25.0 (63.5)
B-2000	(in) (cm)	55.9 (141.9)	116.2 (295.1)	31.6 (80.2)	31.3 (79.5)	13.6 (34.5)	12.1 (30.7)	44.3 (112.5)	5.8 (14.7)	19.8 (50.3)	49.9 (126.7)	4.25 (10.7)	188.2 (478.0)	234.2 (594.8)	56.2 (142.7)	8.4 (21.3)	2.9 (7.3)	35.2 (89.4)	6.6 (16.8)	3.4 (8.6)	57.4 (145.8)	79.0 (200.7)	55.0 (139.7)	31.0 (78.7)
B-3000	(in) (cm)	80.1 (203.4)	153.3 (389.3)	36.7 (93.2)	36.7 (93.2)	17.1 (43.4)	21.5 (54.6)	69.1 (175.5)	5.5 (14.0)	20.2 (51.3)	73.1 (185.6)	4.25 (10.7)	225.3 (572.3)	271.3 (689.1)	58.2 (147.8)	17.5 (44.4)	4.0 (10.1)	35.2 (89.4)	8.9 (22.6)	4.0 (10.2)	58.5 (148.6)	78.9 (200.4)	65.9 (167.4)	25.0 (63.5)

IMPORTANT NOTES:

*(see corresponding dimensions below)

M1 - No Filter Mixbox

M2 - with Filter Mixbox

W1 - with Moisture Limiter or No Filters

W2 - with Filters


CC1 - No Filter Mixbox

CC2 - with Filter Mixbox

DIMENSIONS

Model	AA	BB	CC1*	CC2*	DD	FF	GG	HH	Horizontal Leg Height
B-350	(in) (cm)	25.3 (64.3)	29.2 (74.1)	53.0 (134.6)	87.0 (220.9)	29.0 (73.6)	1.1 (2.7)	27.8 (70.6)	46.0 (116.8)
B-650	(in) (cm)	39.1 (99.3)	37.2 (94.5)	53.0 (134.6)	87.0 (220.9)	40.1 (101.9)	1.1 (2.7)	41.6 (105.7)	46.0 (116.8)
B-1000	(in) (cm)	43.5 (110.5)	44.2 (112.3)	53.0 (134.4)	87.0 (220.9)	41.3 (104.9)	1.1 (2.7)	45.8 (116.3)	46.0 (116.8)
B-2000	(in) (cm)	55.8 (141.7)	56.2 (142.7)	72.0 (182.9)	118.0 (299.7)	56.2 (142.8)	1.1 (2.7)	52.4 (133.1)	46.0 (116.8)
B-3000	(in) (cm)	72.5 (184.2)	58.2 (147.8)	72.0 (182.9)	118.0 (299.7)	43.0 (109.2)	1.1 (2.7)	74.8 (190.0)	46.0 (116.8)

Horizontal Model



ESTIMATED SHIPPING WEIGHTS

Model	B-350		B-650		B-1000		B-2000		B-3000	
	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg
Air Handler*	589	267	994	451	1290	585	1946	883	2877	1305
Filter Section**	118	54	210	95	282	128	407	185	439	199
Filtered Mix Box**	301	137	443	201	539	245	800	363	1156	524
Inlet Hoods	145	66	276	125	346	157	499	226	539	244
Upright Legs***	75	34	99	45	137	62	176	80	214	97
Horizontal Legs***	102	46	102	46	102	46	102	46	102	46
Moisture Limiters****	N/A	N/A	120	54	120	54	210	95	260	118
Skid	147	67	249	113	324	146	486	220	719	326

LEGEND

BD = Bottom Discharge	OA = Outside Air
CE = Control Enclosure	RA = Return Air (Optional)
GC = Gas Connection	TD = Top Discharge
ED = End Discharge	RC = Right Hand Controls
	LC = Left Hand Controls

IMPORTANT NOTES:

- Shipping weights apply to both horizontal and upright models.
- All dimensions and weights are subject to change without notice.
- Control enclosure may be located on either side of air handler. Consult factory submittals for additional details.
- Return Air (RA) is only for Fixed Recirculation (FR) and Air Management (AM) styles.


*Includes Casing, Motor, Control Panel and Manifold

**Includes weight of Filters

***Total Quantity of 4 legs


****Mounted to Intake Hood

Splash Plates



DIMENSIONS					
Model		A	B	C (min)	C (max)
B-350 1K-2K CFM	(in)	25.5	27.6	15.0	20.0
	(cm)	(64.8)	(70.1)	(38.1)	(50.8)
B-350 3K-5K CFM	(in)	25.5	27.6	15.0	20.0
	(cm)	(64.8)	(70.1)	(38.1)	(50.8)
B-650	(in)	37.0	35.1	18.0	27.0
	(cm)	(94.0)	(89.2)	(47.5)	(68.6)
B-1000	(in)	39.8	39.6	18.0	27.0
	(cm)	(101.1)	(100.6)	(47.5)	(68.6)
B-2000	(in)	43.3	43.6	25.0	38.0
	(cm)	(110.0)	(110.7)	(63.5)	(96.5)
B-3000	(in)	48.7	48.7	30.0	45.0
	(cm)	(123.7)	(123.7)	(76.2)	(114.3)

Discharge Heads




DIMENSIONS							WEIGHT	
Model		A	B	C	D	E	lbs	kg
B-350	(in)	16.0	35.5	22.8	13.6	2.0	40	18
	(cm)	(40.6)	(90.2)	(57.9)	(34.5)	(5.1)		
B-650	(in)	23.4	55.7	35.2	25.3	2.0	50	23
	(cm)	(59.4)	(141.5)	(89.4)	(64.3)	(5.1)		
B-1000	(in)	27.8	55.7	35.8	27.8	2.0	84	38
	(cm)	(70.6)	(141.5)	(90.9)	(70.6)	(5.1)		
B-2000	(in)	34.5	77.3	47.7	32.4	2.0	120	54
	(cm)	(87.6)	(196.3)	(121.2)	(82.3)	(5.1)		
B-3000	(in)	37.4	86.8	51.8	37.4	2.0	160	73
	(cm)	(95.0)	(220.5)	(131.6)	(95.0)	(5.1)		

IMPORTANT NOTES:

- Discharge head must be field supported by others.
- Discharge head has manually adjustable horizontal blades.

Discharge Dampers



DIMENSIONS								WEIGHT	
Model		A	B	C	D	E	F	lbs	kg
B-350	(in) (cm)	18.6 (47.2)	15.6 (39.6)	1.5 (3.8)	16.5 (41.9)	13.5 (34.2)	8.0 (20.3)	25	11
B-650	(in) (cm)	28.0 (71.1)	25.0 (63.5)	1.5 (3.8)	26.1 (66.2)	23.1 (58.6)	8.0 (20.3)	51	23
B-1000	(in) (cm)	30.8 (78.2)	27.8 (70.6)	1.5 (3.8)	30.6 (77.7)	27.6 (70.1)	8.0 (20.3)	65	29
B-2000	(in) (cm)	34.3 (87.1)	31.3 (79.5)	1.5 (3.8)	34.6 (87.8)	31.6 (80.2)	8.0 (20.3)	83	38
B-3000	(in) (cm)	39.8 (101.0)	36.8 (93.4)	1.5 (3.8)	39.8 (101.0)	36.8 (93.4)	8.0 (20.3)	111	50

IMPORTANT NOTES:

- Discharge dampers do not mount directly to air handler; they mount downstream of air handler in duct work.

Filters

For Filter Sections

Permanent Aluminum Mesh Pleated / Polyester*			
Model		Size	Quantity
B-350	(in) (cm)	25 x 25 x 2 (63.5 x 63.5 x 5.1)	2
B-650	(in) (cm)	20 x 20 x 2 (50.8 x 50.8 x 5.1)	6
B-1000	(in) (cm)	24 x 20 + 20 x 20 [5 each] (60.9 x 50.8 + 50.8 x 50.8)	10
B-2000	(in) (cm)	25 x 25 x 2 (63.5 x 63.5 x 5.1)	12
B-3000	(in) (cm)	24 x 20 x 2 (60.9 x 50.8 x 5.1)	24


For Inlet Hoods

Poly Panel			
Model		Size	Quantity
B-350	(in) (cm)	25 x 25 x 1 (63.5 x 63.5 x 2.5)	2
B-650	(in) (cm)	20 x 20 x 1 (50.8 x 50.8 x 2.5)	6
B-1000	(in) (cm)	24 x 20 x 1 + 20 x 20 x 1 [5 each] (60.9 x 50.8 x 2.5 + 50.8 x 50.8 x 2.5)	10
B-2000	(in) (cm)	18 x 24 x 1 (45.7 x 60.9 x 2.5)	18
B-3000	(in) (cm)	25 x 75 x 1 (63.5 x 190.5 x 2.5)	6

IMPORTANT NOTES:

*Filter Sections, Filtered Mix Boxes use the same quantity and size.

Roof Curbs



DIMENSIONS							WEIGHT*		WEIGHT**	
Model		A	B	C	D	E	lbs	kg	lbs	kg
B-350	(in) (cm)	25.9 (65.8)	78.2 (198.6)	22.9 (58.2)	127.1 (322.8)	48.9 (121.8)	96	43	140	63
B-650	(in) (cm)	39.3 (99.8)	102.5 (260.3)	36.3 (96.8)	155.5 (395.1)	51.4 (128.1)	133	60	179	81
B-1000	(in) (cm)	45.1 (114.6)	96.3 (244.6)	42.1 (111.6)	143.2 (363.8)	47.9 (119.2)	130	59	173	78
B-2000	(in) (cm)	51.9 (131.8)	114.7 (291.3)	48.9 (128.8)	182.7 (464.1)	68.0 (172.7)	153	69	216	97
B-3000	(in) (cm)	76.1 (193.3)	151.8 (385.6)	73.1 (190.3)	215.4 (547.1)	64.6 (161.5)	210	95	268	121

IMPORTANT NOTES:

- *Blower and Burner Section
- **Blower, Burner and Filter Mixbox
- Curb is shipped unassembled.
- A & B are outside dimensions for the top of the curb.
- Curb material is 14 gauge galvanized steel.
- Nuts and bolts (3/8" x 1") are furnished.
- Caulk all joints before assembling. (Caulk provided by others).
- Dimensions D & E only applicable when Filtered Mixbox option is utilized.

B-Series Selection Guide

Airflow CFM (m3/h)	Model	Motor HP at 1" ESP	dBA at Noted External Static Pressure (in wc)**			Heat Output at Maximum Temperature Rise (Btu/h) X 1000		Minimum Inlet Gas Pressure in wc	Minimum Inlet Gas Pressure in wc (mbar)***
			0	0.5	1	NG	LPG		
1,000 (1,700)	B-350	1	48	72	72	119	97	9.6	23.9
2,000 (3,400)	B-350	3	78	80	81	238	194	6.7	16.7
3,000 (5,100)	B-350	2	61	68	72	356	292	5.7	14.2
4,000 (6,800)	B-350	3	66	69	73	475	389	8.3	20.7
5,000 (8,500)	B-350	5	72	72	75	594	486	8.5	21.2
5,000 (8,500)	B-650	3	64	75	80	594	486	6.3	15.7
6,000 (10,200)	B-650	5	62	73	80	713	583	5.8	14.4
7,000 (11,900)	B-650	5	60	71	78	832	680	6.5	16.2
8,000 (13,600)	B-650	5	61	72	78	950	778	7.7	19.2
9,000 (15,300)	B-650	7.5	65	73	79	1,069	875	9.2	22.9
10,000 (17,000)	B-650	10	66	74	79	1,188	972	10.9	27.1
11,000 (18,700)	B-1000	7.5	67	69	73	1,307	1,069	6.0	14.9
12,000 (20,400)	B-1000	7.5	69	71	71	1,426	1,166	6.9	17.2
13,000 (22,100)	B-1000	10	71	73	74	1,544	1,264	7.9	19.7
14,000 (23,800)	B-1000	10	72	75	76	1,663	1,361	8.9	22.1
16,000 (27,200)	B-1000	15	76	78	79	1,901	1,555	11.1	27.6
18,000 (30,600)	B-1000	20	79	80	81	2,138	1,750	13.7	34.1
16,000 (27,200)	B-2000	10	65	72	73	1,901	1,555	6.1	15.2
18,000 (30,600)	B-2000	15	67	72	77	2,138	1,750	6.0	14.9
20,000 (34,000)	B-2000	15	70	73	77	2,376	1,944	6.8	16.9
22,500 (38,200)	B-2000	20	73	74	78	2,673	2,187	8.0	19.9
25,000 (42,500)	B-2000	25	76	76	79	2,970	2,430	9.4	23.4
27,500 (46,700)	B-2000	30	78	79	80	3,267	2,673	11.1	27.6
30,000 (51,000)	B-2000	40	80	81	84	3,564	2,916	13.0	32.3
27,500 (46,700)	B-3000	25	82	83	85	3,267	2,673	9.0	22.4
30,000 (51,000)	B-3000	25	84	85	86	3,564	2,916	10.5	26.1
32,500 (55,200)	B-3000	30	86	87	88	3,861	3,159	12.2	30.4
35,000 (59,500)	B-3000	40	88	88	89	4,158	3,402	14.1	35.1
37,500 (63,700)	B-3000	40	90	90	90	4,455	3,645	13.4	33.3
40,000 (68,000)	B-3000	50	91	91	92	4,752	3,888	13.8	34.3

IMPORTANT NOTES:

All information provided in this table is based on the assumption that unit is installed at an altitude below 2000 feet (609.6 meters).

CF = Consult Factory

** dBA is measured at 10' (3 m) from unducted discharge.

*** Maximum Inlet Gas Pressure: All Models = 5 psi (344.7 mbar)

Thank You for Your Business!

Bananza®

1100 Seven Mile Road NW
Comstock Park, MI 49321
Telephone: +1.616.726.8800
Toll Free: 800.255.3416
Fax: +1.616.784.0435
www.bananza.com

This product is not for residential use.

This document is intended to assist licensed professionals in the exercise of their professional judgment.

© 2017 Roberts Gordon LLC

All rights reserved. No part of this work covered by the copyrights herein may be reproduced or copied in any form or by any means – graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems – without written permission of Roberts Gordon LLC. All information contained in this document is subject to change without notice.